

Pyrogel ® XTF Revision Date: 07/21/11

1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY

Product Name: Pyrogel® XTF

Synonyms: Silica aerogel materials

Use of the Substance/Preparation: High performance insulation material

Manufacturer: Aspen Aerogels, Inc. Address: 30 Forbes Road

Northborough, MA 01532

Telephone: (508) 691-1111

Emergency Telephone Number: 800-535-5053 US & Canada (INFOTRAC)

352-323-3500 International

MSDS Prepared by: EHS

Phone Number of Preparer: 508-691-1111

2. HAZARDS IDENTIFICATION

Appearance and

Grey fabric material with no characteristic odor. Under certain conditions, product may have

faint ammonia-like odor.

Emergency

Odor:

Inhalation of excessive amounts of dust from the product may cause mechanical irritation to the

Overview: respiratory tract. Dermal contact may cause mechanical irritation.

POTENTIAL HEALTH EFFECTS

Inhalation: Inhalation of airborne dusts may cause mechanical irritation of the upper respiratory tract.

Exposure to dust from this product can produce a drying sensation and mechanical irritation of

the eyes.

Skin Contact: Skin contact with dust from this product can produce a drying sensation and mechanical

irritation of the skin and mucous membranes.

Skin Absorption: Material will not absorb through skin.

Ingestion: This material is not intended to be ingested (eaten). If ingested in large quantity, the material

may produce mechanical irritation and blockage

Acute Health

Dust from this product is a physical irritant, and may cause temporary irritation or scratchiness

of the throat and / or itching and redness of the eyes and skin.

Chronic Health

Hazards:

Hazards:

In 2006, the International Agency for Research on Cancer (IARC) reclassified titanium dioxide as "possibly carcinogenic to humans" (Group 2B) based on animal experiments. In the draft Titanium Dioxide Monograph (Vol. 93), IARC concluded that the human carcinogenic studies "do not suggest an association between occupational exposure as it occurred in recent decades in western Europe and North America and risk of cancer." See Section 11 for a full discussion.

Medical Conditions Aggravated by Excessive inhalation of dust may aggravate pre-existing chronic lung conditions including, but not limited to, bronchitis, emphysema, and asthma. Dermal contact may aggravate existing

Exposure: dermatitis.

CARCINOGENICITY

CARCINOGENICITI						
Component	ACGIH	NTP	IARC			
Titanium Dioxide	A4	Not Listed	2B			
Fibrous Glass (textile grade)	A4	Not Listed	3			
Aluminum Trihydrate	Not Listed	Not Listed	None			
Amorphous Silica	NA	Not Listed	None			



Pyrogel ® XTF Revision Date: 07/21/11

SECTION 2 NOTES: This product is composed of synthetic amorphous silica dioxide, often referred to as silica gel or amorphous precipitated silica. Amorphous silica should not to be confused with crystalline silica. Epidemiological studies indicate low potential for adverse health effects from exposure to amorphous silica.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS Number	Percent	EINECS Number	EU Classification
Methylsilylated Silica	68909-20-6	40-55	272-697-1	None
Synthetic vitreous fibers	NA	40-50	Not Assigned	None
Titanium Dioxide	1317-80-2	4-6	236-675-5	None
Aluminum Trihydrate	21645-51-2	0-5	244-492-7	None
Magnesium Hydroxide	1309-42-8	0-5	215-170-3	None
Proprietary Pigment ^a	NA	<1	NA	None

^aProduct contains <1% of a proprietary pigment whose elemental components include iron and manganese.

4. FIRST AID MEASURES

Eye Contact: Immediately wash with large amounts of water for at least 15 minutes, occasionally lifting lids.

If irritation occurs and persists, get medical treatment.

Skin Contact: Wash skin thoroughly with soap and water until clean. The soap will act as a surfactant to

remove the material. Remove contaminated clothing and shoes. Wash clothing before reuse.

Obtain medical attention if symptoms occur.

Ingestion: Material will pass through the body normally. Obtain medical attention if symptoms occur.

Inhalation: Remove to fresh air. Drink water to clear throat and blow noise to remove dust. Obtain

medical attention if ill effects persist.

5. FIRE-FIGHTING MEASURES

5.1 FLAMMABILITY PROPERTIES

Flammable	No
Auto ignition Temperature	Not Applicable
Flash Point	Not Applicable
Flammability Limits: (Lower Explosive Limit)	Not Applicable
Flammability Limits: (Upper Explosive Limit)	Not Applicable
Explosion Data – Sensitivity to impact	Not sensitive
Explosion Data – Sensitivity to static discharge	Not sensitive

5.2 EXTINGUISHING MEDIA:

Use media suitable for surrounding fire and that are appropriate to the surrounding environment; normal fog nozzle water application and/or exclusion of air is typically suitable for extinguishing this product in blanket form.

5.3 PROTECTION FOR FIRE FIGHTERS

Special Fire Fighting Procedures: Normal fire fighting procedures should be followed to avoid inhalation of smoke

and gases produced by a fire.

Unusual Fire and Explosion

Hazards:

Product is a super-insulation material. Rolls of material can retain heat within internal layers and re-ignite combustible materials if heat is not removed.

Hazardous Decomposition and/or

Combustion Products:

Primary combustion products are carbon monoxide and carbon dioxide. Other



Pyrogel ® XTF Revision Date: 07/21/11

undetermined products could be released in small quantities.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Minimize dust generation. Ensure adequate ventilation. Use personal protective

equipment as necessary.

Material is not soluble. Do not flush into surface water or sanitary sewer system. **Environmental Precautions:**

Contain and collect released material for proper disposal. Dry vacuuming is the **Methods for Cleaning Up:**

preferred method of cleaning up.

7. HANDLING AND STORAGE

Handling Aerogel blankets will generate dust when handled. Workplace exposure to all dusts should be

> controlled with standard industrial hygiene practices. Dry vacuuming is the preferred method for cleaning up dust. Because aerogel dust is hydrophobic, water is not effective as a dust control agent.

Storage Aerogel blankets should be kept in their packaging until they are ready to be used. Unpack the material

in the work area. This will help to minimize the area where dust exposure may occur. Trimmed

material and scrap should be promptly packed in disposal bags.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Exposure Limit Values

There are no exposure limits identified for the main product component, classified as synthetic amorphous silica. Exposure limits for synthetic amorphous silica are based on silica (CAS No. 7631-86-9).

CAS Number 7631-86-9	Component Name Silica, Amorphous	Exposure Limits Germany TRGS 900 UK WEL US OSHA PEL (TWA) ^a : US ACGIH ^b	4 mg/m³ (inhalable fraction) 6 mg/m³ (total inhalable fraction) 2.4 mg/m³ (respirable fraction) 15 mg/m³ (total dust) 5 mg/m³ (respirable fraction) 10 mg/m³ (inhalable) 3 mg/m³ (respirable)
1317-80-2	Titanium Dioxide	Germany TRGS 900 UK WEL US OSHA PEL (TWA): US ACGIH:	1.5 mg/m ³ (respirable dust) 10 mg/m ³ (total inhalable fraction) 4 mg/m ³ (respirable fraction) 10 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction) 10 mg/m ³ (total dust)
21645-51-2	Aluminum Trihydrate	US OSHA PEL (TWA) ^a : US ACGIH ^b	15 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction) 10 mg/m ³ (inhalable) 3 mg/m ³ (respirable)
NA	Continuous filament glass fibers	US ACGIH US OSHA	1.0 fibers/cc ^c 5 mg/m ³ (inhalable) 10 mg/m ³ (total dust) 5 mg/m ³ (respirable fraction)

^a The US OSHA standard for amorphous silica is: (80 mg/m³)/(%SiO2). The NIOSH Sampling Method 7501 for Amorphous Silica calculates the %SiO2 based on the percentage of crystalline silica in the sample. Because the percentage of crystalline silica in aerogel is 0%, the particulate limit applies.

^b US ACGIH based on Particles Not Otherwise Specified (PNOS)

8.2 Exposure Control

 $^{^{}c}$ Respirable fibers: length >5 μ m; aspect ratio \geq 3:1, as determined by the membrane filter method at 400–450X magnification (4-mm objective), using phase-contrast illumination. US NIOSlengthµm, width <3 µm diameter and length:width ratios ≥3.



Pyrogel ® XTF Revision Date: 07/21/11

Ventilation: Local exhaust in accordance with general industrial hygiene practices is recommended to

control dust.

Respiratory Protection: A properly fitted, NIOSH or CE approved respirator should be worn when ventilation is

unavailable or inadequate to maintain airborne concentrations below applicable occupational exposure limits. A respiratory protection program that meets applicable local regulations should be implemented whenever workplace conditions warrant use of

a respirator.

Hand Protection Silica aerogels are hydrophobic (repel water) and may cause drying and irritation of the

skin, eyes, and mucous membranes. For this reason, nitrile, latex, or other impermeable

gloves should be worn when handling aerogel blankets.

Eye Protection: Safety glasses. Chemical goggles could be worn to provide greater protection from dust.

Skin Protection: Long-sleeved, long-legged work clothes are also advised. Disposable coveralls should

be considered to minimize skin exposure and track out of aerogel dusts into adjacent

areas.

Work Hygienic

Practices

Keep materials packaged until just prior to use. Die cut in preference to rotary or other cutting methods. Dry vacuum with proper filtration preferred to sweeping. Wash thoroughly after using the product. Wash clothing if dust conditions present. Wash

hands before eating or drinking.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Grey fabric blanket; material is hydrophobic (repels water)

Odor: No characteristic odor. Under certain conditions, such as high storage temperatures, product

may have faint ammonia-like odor.

Odor Threshold Reported ammonia threshold vary widely: 0.6 to 53 ppm

pH: Not applicable.
Specific Gravity: Not applicable
Boling Point/Range: Not applicable.
Freezing Point Not applicable
Flash Point: Not applicable.
Flammability (solid, gas): Not applicable.
Explosive Properties: Not applicable.
Oxidizing Properties: Not applicable.
Not applicable.

Explosive Properties:
Oxidizing Properties:
Vapor Pressure:
Vapor Density (air = 1)
Solubility:
Viscosity:
Evaporation Rate:
Coeffiient of water/oil
Not applicable.
Not applicable.
Not applicable.
Not applicable.
Not applicable.

distribution

10. STABILITY AND REACTIVITY

Chemical Stability: Stable

Conditions to Avoid: Prolonged exposure to temperatures above the recommended use temperature as noted

in technical data sheet. Avoid conditions that produce large quantities of dust dispersed

in air.

Materials to Avoid: Avoid strong acids and bases.



Pyrogel ® XTF Revision Date: 07/21/11

Hazardous Decomposition Products Under recommended usage conditions, hazardous decomposition products are not expected. Hazardous decomposition products, including carbon monoxide and other productions of combustion, may occur as a result of oxidation, heating or reaction with another material.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Dust may cause mechanical irritation and dryness to eyes and skin.

Synthetic Amorphous Silica

 Oral LD50:
 >5,000 mg/kg

 Inhalation LC50:
 >2,000 mg/m³

 Dermal LD50:
 >3,000 mg/kg

Eye Irritation: Synthetic amorphous silica and silicates are not irritating to skin and eyes under experimental

conditions, but may produce dryness following prolonged and repeated exposure.

Skin Irritation: Synthetic amorphous silica and silicates are not irritating to skin and eyes under experimental

conditions, but may produce dryness following prolonged and repeated exposure.

Titanium Dioxide

Oral LD50: >5,000 mg/kg

Inhalation LC50: $>6,820 \text{ mg/m}^3 \text{ (ALC/4 hour rat)}$

Dermal LD50: >10,000 mg/kg (rabbit)

Eye Irritation: Slight irritation Skin Irritation: Slight irritation

Aluminum Trihydrate

Oral LD50: >5,000 mg/kg (rat)
Eye Irritation: Slightly irritating
Non-irritating

CHRONIC TOXICITY

Some studies of long term amorphous silica dust exposures indicate a potential for decreased lung function. In surveyed studies, this effect is characterized as compounded by smoking. Additionally, surveyed studies characterize the decreased lung function effect as reversible on discontinuation of exposure. There is no available data for this product on skin sensitization, respiratory sensitization, reproductive toxicity, teratogencity, embryotoxicity, mutagenicity or synergisticity.

CARCINOGENICITY

In February 2006, the International Agency for Research on Cancer (IARC) reclassified titanium dioxide (TiO₂) to "possibly carcinogenic to humans" (Group 2B). In the initial Titanium Dioxide Monograph (1989), IARC had concluded that there was limited evidence of carcinogenicity in experimental animals and inadequate evidence of carcinogenicity of titanium dioxide in humans (Group 3).

The recent IARC classification for TiO₂ was based on *inadequate evidence* in humans and *sufficient evidence* in experimental animals. IARC considers there to be *inadequate evidence of carcinogenicity* when the available studies are of "insufficient quality, consistency or statistical power to permit a conclusion" or "no data on cancer in humans are available". IARC considers there to be *sufficient evidence of carcinogenicity* in experimental animals when two or more independent studies in one species carried out at different times or in different laboratories or under different protocols" show evidence of carcinogenicity. The Group 2B for TiO₂ classification was based on three animal studies and four human studies. In the Titanium Dioxide Monograph (Vol. 93), IARC concluded that the human carcinogenic studies "do not suggest an association between occupational exposure as it occurred in recent decades in western Europe and North America and risk of cancer."



Pyrogel ® XTF Revision Date: 07/21/11

US OSHA currently does not regulate titanium dioxide as a carcinogen (ref: OSHA Letter of Interpretation to North American Refractories Co, 11/19/97). The US National Institute for Occupational Safety & Health (NIOSH) currently recommends that titanium dioxide be considered a potential occupational carcinogen. NIOSH based this recommendation on a chronic inhalation study of rats exposed to 250 mg/m³ of fine titanium dioxide. NIOSH presently is reviewing the available toxicity data on titanium dioxide, as well as other relevant health data associated with particle surface area, with the intent of developing new workplace recommendations for titanium dioxide, including recommended exposure limits (RELs). NIOSH has indicated that the tumorigenic effects of titanium dioxide do not appear to be chemical-specific or a direct action of the chemical substance itself. Rather, these effects appear to be a function of particle size and surface area acting through a secondary genotoxic mechanism associated with persistent inflammation. Titanium dioxide is **NOT** included in California's List of Chemicals Known to the State to Cause Cancer or Reproductive Toxicity dated March 21, 2008. The American Conference of Governmental Industrial Hygienists (ACGIH) considers titanium dioxide to be not classifiable as a human carcinogen (A4).

According to the manufacturer, the fiberglass in this product is considered textile grade fibrous glass and it is not classified as a carcinogen by ACGIH, IARC, NTP or OSHA.

The International Agency for Research on Cancer (IARC) considers synthetic amorphous silica to be not classifiable as to its carcinogenicity to humans (Group 3).

NOTE TO SECTION 11: Toxicological information for synthetic amorphous silica is based on literature review.

12. ECOLOGICAL INFORMATION

Aquatic Toxicity

Synthetic Amorphous Silica Fish: LC50 > 10,000 mg/L (Brachydanio rerio: 96 hour), Method OECD 203

Daphnia magna: EC50 > 10,000 mg/l (24 hours), Method OECD 202

Titanium Dioxide Fish: LC50 > 1,000 mg/L (fathead minnow 96 hour)

Aluminum Trihydrate Fish: LC50 > 10,000 mg/L

Mobility None expected due to insoluble nature of product.

Persistence and Biodegradability Not applicable for inorganic material.

Bioaccumulative PotentialNone expected due to insoluble nature of product.

Other Adverse Effects None expected.

NOTE TO SECTION 12: Ecological information is based on literature review for synthetic amorphous silica (CAS No. 7631-86-9). Information on aluminum trihydrate based on manufacturer's information.

13. DISPOSAL CONSIDERATIONS

Dispose in an approved landfill in accordance with federal, state / provincial, and local regulation. Cover promptly to avoid blowing of dust. This product is not regulated as a hazardous waste under US RCRA regulations.

14. TRANSPORT INFORMATION

Shipping Name: Not regulated for transport

Hazard ClassNoneUN NumberNonePacking GroupNoneRequired Label(s)NoneMarine PollutantNoAdditional InformationNone



Pyrogel ® XTF Revision Date: 07/21/11

15. REGULATORY INFORMATION

EU REGULATORY INFORMATION

Product is not classified as a dangerous material or preparation as defined in EC Directives 67/548/EEC or 1999/45/EC. Aerogel insulation blankets are considered an article, not a substance or preparation, under the REACH directive.

U.S. FEDERAL REGULATIONS

CERCLA (Comprehensive Response Compensation and Liability Act): Product is not classified as hazardous or reportable under this requirement.

SARA TITLE III (Superfund Amendments and Reauthorization Act): Product is not classified as hazardous or reportable under this requirement.

311/312 HAZARD CATEGORIES: Materials in this product are classified as hazardous or reportable under this requirement.

313 REPORTABLE INGREDIENTS: Materials in this product are not classified as hazardous or reportable under this requirement.

TSCA: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

STATE REGULATIONS: Materials in this product appear on the following state hazardous substance lists: CA, IN, KY, MA, MN, NC, NJ, OR, PA. Check individual state requirements.

CANADIAN REGULATIONS: This product has been classified according to the hazard criteria of the Controlled Products Regulation (CPR) and the MSDS contains all the information required by the CPR. All chemical substances in this product are included on or exempted from the Canadian Domestic Substance List (DSL). Amorphous silica (CAS No. 7631-86-9) is listed on the WHMIS Ingredient Disclosure List at a concentration threshold of 1%. Titanium dioxide (CAS No. 1344-28-1) is listed at a concentration threshold of 0.1%. Titanium Dioxide is a Class D, Division 2, Subdivision A controlled product under WHMIS.

16. OTHER INFORMATION

NFPA HAZARD CLASSIFICATION HMIS HAZARD CLASSIFICATION Health 1 Health **Flammability** 0 **Flammability** 0 Reactivity 0 Reactivity Other N/A **Protection** Please refer to Section 8.

Section 11 Titanium Dioxide Epidemiological References: 1) Fryzek JP, et. al. [2003]. A cohort study among titanium dioxide manufacturing workers in the United States. J Occup Environ Med 45:400-409. 2) Boffeta et. al. [2004]. Mortality among workers in the titanium dioxide production industry in Europe. Cancer Causes Control 15:697-706.

Synthetic Amorphous Silica Toxicity Information Reference: United Nations Environmental Programme (UNEP), Organization for Economic Cooperation & Development (OECD) Screening Information Data Set (SIDS) Initial Assessment Report, Synthetic Amorphous Silica, July 23, 2004.

Revision Summary: Added additional information for Canadian Controlled Product Regulation.

DISCLAIMER: The information herein is presented in good faith and believed to be accurate as the effective data given. However, no warranty, expressed or implied, is given. It is the user's responsibility to ensure that its activities comply with Federal, State or Provincial, and local laws.